

ECO-BOND Adhesives, LLC 1343 E.Wisconsin Ave. #110 Pewaukee, WI 53072 800-326-8102 www.ecobondit.com



Non-Toxic Caulk, Construction Adhesive, Sealant, and Silicone Replacement

PRODUCT SPECIFICATIONS:

- Zero VOC's off gassed during curing process
- 100% NON-Toxic, no solvents
- AAMA Certified
- Waterproof
- Certified Hypoallergenic
- Bonds & Seals Fully Submerged
- Exceeds all CA Standards
- Chemically impervious to all mold and mildew
- No toxic odor
- Paintable within in 2 hours
- Tack Free 45 minutes
- Application Temperature is -35° to +140° F
- No Prop 65 listed materials
- UV resistant
- Earns LEED and NAHB Green Building Points
- Non-Shrinking
- Safe to use indoors
- Non-Flammable
- Non-petroleum based
- Easy to tool
- Compatible with SBS Flashing

PERFORMANCE STANDARDS:

- Exceeds the requirements of ASTMC920, Type S, Grade NS, Class 50, Use T, NT, M, and G
- Federal Specifications TT-S-00230C, Type II, Class A
- Meets California Requirements for Prop 65 and All Clean Air Act Standards

TECHNICAL SPECIFICATIONS:

Shear strength: 190 psi
Tensile strength: 200 psi

• Elongation: 300% - 400%

• Cure Rate: 1/4" Bead per 24 Hrs

Movement Capability: 25%

 UV Rating: No discoloration or change in appearance after 2500 hrs. of UV

Sag: NoneStaining: None

BONDS & SEALS TO:

Aluminum Plaster
Asphalt Plastic
Block and Brick Plywood
Cement Based Products Polystyrene
Ceramic Polyurethane

PVC Concrete Coated Metal Resins Rubber Copper Sheet Metal Cork Drywall Siding **Fiberglass** Slate Foam Steel Galvanized Metal Stone Stucco Glass

Laminate Treated Wood
Marble Two Non-porous
Metal Surfaces
Mirrors Vinyl
Painted Surfaces Windows

Wood

STOCK SIZES:

• 10.1 Ounce Tube

SPECIAL ORDER:

- 2 ounce, 29 ounce, 2 Gallon, 5 Gallon & 55 Gallon
- Color matching available

Paneling

1-800-ECO-8102

www.ecobondit.com